



Линейные насосы и компрессоры



SMG4



LM 15 DC



YP-20 DU



YP-15 A

Вакуум								Размеры	
Модель	Двигатель		Скорость потока, л/мин@мбар			Вакуум _{max}		а x в x с	
	В	Тип*	0	-100	-200	непрер. режим	прер. режим		
SMG 4	230/50	LM	1,4	0,9	0,5	-300	-300	46 x 53 x 72	
SMG 4	12 / 24**	LM	1,3	0,8	0,3	-250	-250	46 x 53 x 72	
LM 15	230/50	LM	16,0	12,5	7,5	-300	-350	65 x 111 x 107	
LM 15	12 / 24**	LM	15,0	12,0	5,3	-200	-280	76 x 111 x 107	
LM 22	230/50	LM	22,0	16,0	6,0	-250	-260	65 x 111 x 107	
LM 22	12 / 24**	LM	20,0	15,0	5,6	-200	-260	76 x 111 x 107	
YP-6DU	230/50	LM						77 x 116 x 110	
YP-150DU	230/50	LM						77 x 116 x 110	
YP-20DU	230/50	LM						77 x 116 x 110	
YP-6A	230/50	LM						111 x 128 x 148	
YP-15A	230/50	LM						111 x 128 x 148	
YP-20A	230/50	LM						111 x 128 x 148	
YP-6V	230/50	LM	13,0	5,0		-150	-150	111 x 128 x 148	
YP-15V	230/50	LM	25,0	14,0	3,0	-200	-200	112 x 128 x 148	
YP-20V	230/50	LM	31,0	19,0	7,0	-200	-200	113 x 128 x 148	
4015SE	230/50	LM	31,0	10,0		-100	-100	86 x 117 x 128	
4025SE	230/50	LM	62,0	42,0	24,0	-270	-340	86 x 117 x 128	
YP-30DU	230/50	LM						104 x 136 x 160	
YP-40DU	230/50	LM						104 x 136 x 160	
YP-50DU	230/50	LM						104 x 136 x 160	
YP-30VC	230/50	LM	45,0	31,0	20,0	-200	-200	163 x 175 x 207	
YP-40VC	230/50	LM	59,0	43,0	25,0	-200	-200	163 x 175 x 207	
YP-50VC	230/50	LM	85,0	58,0	30,0	-200	-200	163 x 175 x 207	
YP-60VC	230/50	LM	88,0	67,0	42,0	-200	-200	163 x 175 x 207	
YP-70VC	230/50	LM	115,0	88,0	60,0	-200	-200	163 x 175 x 207	
LP-30A	230/50	LM						200 x 174 x 227	
LP-40A	230/50	LM						200 x 174 x 227	
LP-60HN	230/50	LM						200 x 174 x 227	
LP-80HN	230/50	LM						218 x 179 x 227	
LP-100H	230/50	LM						218 x 179 x 227	
LP-120H	230/50	LM						218 x 179 x 227	
LP-150H	230/50	LM						252 x 194 x 254	
LP-200H	230/50	LM						252 x 194 x 254	

* LM - линейный привод. ** Генератор переменного тока

Вес		Давление							
Вес кг	Модель	Двигатель		Скорость потока, л/мин @ мбар				Давление	
		В	Тип*	0	100	200	400	непрер. режим	прер. режим
0,2	SMG 4	230/50	LM	1,4	1,0	0,8	0,2	450	450
0,2	SMG 4	12 / 24*	LM	1,3	1,0	0,7	0,1	450	450
1,0	LM 15	230/50	LM	16,0	12,5	8,4		300	400
1,0	LM 15	12 / 24*	LM	15,0	12,0	6,6		200	320
1,0	LM 22	230/50	LM	22,0	16,0	8,0		250	300
1,0	LM 22	12 / 24*	LM	20,0	15,0	5,6		200	260
1,1	YP-6DU	230/50	LM	13,0	6,0			150	150
1,2	YP-15DU	230/50	LM	25,0	15,0	5,0		200	200
1,2	YP-20DU	230/50	LM	31,0	20,0	9,0		200	200
2,1	YP-6A	230/50	LM	13,0	6,0			150	150
2,4	YP-15A	230/50	LM	25,0	15,0	5,0		200	200
2,4	YP-20A	230/50	LM	31,0	20,0	9,0		200	200
2,1	YP-6V	230/50	LM	13,0	6,0			150	150
2,4	YP-15V	230/50	LM	25,0	15,0	5,0		200	200
2,4	YP-20V	230/50	LM	31,0	20,0	9,0		200	200
1,2	4015SE	230/50	LM	31,0	10,0			100	100
1,5	4025SE	230/50	LM	62,0	44,0	28,0		280	380
2,3	YP-30DU	230/50	LM	59,0	37,0	15,0		200	200
2,5	YP-40DU	230/50	LM	78,0	49,0	20,0		200	200
2,8	YP-50DU	230/50	LM	84,0	56,0	29,0		220	220
4,8	YP-30VC	230/50	LM	45,0	35,0	25,0		200	200
5,1	YP-40VC	230/50	LM	59,0	48,0	30,0		200	200
5,5	YP-50VC	230/50	LM	85,0	61,0	38,0		200	200
5,9	YP-60VC	230/50	LM	88,0	70,0	52,0		200	200
6,2	YP-70VC	230/50	LM	115,0	93,0	73,0		200	200
5,0	LP-30A	230/50	LM	65,0	40,0	18,0		200	200
5,5	LP-40A	230/50	LM	68,0	47,0	27,0		200	200
6,0	LP-60HN	230/50	LM	100,0	80,0	60,0		200	200
8,3	LP-80HN	230/50	LM	148,0	112,0	76,0		250	250
8,3	LP-100H	230/50	LM	160,0	130,0	95,0		250	250
8,3	LP-120H	230/50	LM	165,0	140,0	120,0		250	250
11,0	LP-150H	230/50	LM	250,0	200,0	150,0		300	300
11,0	LP-200H	230/50	LM	300,0	250,0	200,0		300	300



4025 SE



YP-40 VC



LP-60HN



LP-80HN